Product specifications

Consumer range

鋼鐵超人
超耐磨抗蝕磁護劑®

渦輪增壓引擎磁護專用

Super Friction Proofing®

Wynn's 新一代高科技奈米超合成配方，有別於傳統金屬化合物的引擎耐磨修補劑，為現代低 SAPS 潤滑油需求之功能回復及加強劑，保護引擎、渦輪不受損，不添加任何傷害觸媒轉化器之有毒化學物，符合歐洲 ACEA 及美國 API 最新低磷硫環保規範，守護您的愛車也守護地球。

於引擎啟動瞬間形成保護膜，牢牢密封金屬保護引擎，更於汽車行駛中持久保護汽缸和活塞，免除每分鐘千次上下刮擦損害，特殊油泥抑制配方，去除及防止油泥產生，大幅降低油道阻塞及渦輪損耗。

特性

- ✓ 保護和增強現代引擎性能。
- ✓ 降低引擎曲軸、汽缸、活塞及渦輪軸摩擦和磨損，保持金屬表面良好的狀態。
- ✓ 抑制油泥和沉積物形成，防止油道管及渦輪阻塞。
- ✓ 防止油品氧化和稠化，延長油品壽命。
- ✓ 減少汽油或柴油的消耗。
- ✓ 無副作用不含磷或固體潤滑劑（鉬、鐵氟龍、石墨...）不傷害及堵塞觸媒轉化器及金屬零件。
- ✓ 相容於所有礦物油基、合成油基、單級與複級機油，符合SAPS和低SAPS標準應用。

適用

- ✓ 所有汽油、柴油、液化石油氣和油電混合引擎(裝配或無裝配渦輪增壓器)。
- ✓ 尤其推薦用於渦輪增壓器引擎，或自動怠速熄火系統引擎，亦適用於舊式老引擎。
- ✓ 高里程數的駕駛在換油區間若添加本品於機油是非常有效，能提昇機油性能和保護引擎。

技術資料

外觀	：褐色液體
比重, 20℃	：0.877 kg/dm³
黏度, 40℃	：98 mm²/s
黏度, 100℃	：13 mm²/s
折射率, 20℃	：1.48

使用方法

- ✓ 每次換機油時同機油一同添加，亦可於換機油區間添加，增強效能。
- ✓ 2.5~5公升的機油添加1瓶(325ml)。

包裝

PN 66963 – 12x325 ml – EN/FR/DE/NL/HU/ES

WOFOIL 維風實業股份有限公司
WELL FROM INDUSTRIAL INC.
電 話：07-332-6920
傳 真：07-339-0825
www.wofoil.com.tw
80241高雄市苓雅區中興街159號
wellfrom@wofoil.com.tw

The data concerning properties and applications of the indicated products are offered in good faith and are based on our research and practical experiences. Due to the versatility of the application possibilities, it is impossible to mention all details and we do not assume any obligations or responsibilities resulting from this. When a new edition appears due to the technical development, the preceding data are no longer valid.